

View Online at <https://aerobasegroup.com/nsn/5935-00-775-3715>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

0.938 inches

Overall Diameter:

0.578 inches

Environmental Protection:

Pressure proof

Distance From Mounting Shoulder To Front Face:

0.250 inches

Mounting Facility Thickness:

Between 0.087 inches and 0.093 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

2

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

600.0 all mating ends single contact grouping

Contact Maximum Frequency Rating:

500.0 megahertz all mating ends single contact grouping

Shell Type:

Solid

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Thread Size:

0.375 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping and silver all mating ends single contact grouping

Insert Material:

Plastic tetrafluoroethylene all mating ends

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Coaxial pin all mating ends single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.002 gold grains, troy and 0.002 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0