## NSN 5935-00-775-5711

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-775-5711

**Body Style:** Straight edge type **Overall Length:** 3.695 inches **Overall Height:** 0.676 inches **Overall Width:** 0.496 inches **Environmental Protection:** Vibration proof **Unthreaded Mounting Hole Diameter:** 0.128 inches **Distance Between Mounting Facility Centers:** 3.406 inches **Board Accommodated Length:** 2.966 inches single board **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Bridged contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Contact **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Tab, solder lug single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-14, type mdg military specification single material response single mating end

**Included Contact Quantity:** 

18 single mating end single contact grouping

## NSN 5935-00-775-5711

Electrical Receptacle Connector - Page 2 of 2



## Included Contact Type: Flat pin single mating end single contact grouping Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.018 gold grains, troy Precious Material: Gold Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig:

A039b0

Mil-m-14 spec.

Mil-std (military Standard):