Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-775-9058

Body Style:

Pcb, external coupling

Overall Length:

Between 0.412 inches and 0.453 inches

Overall Height:

Between 0.422 inches and 0.454 inches

Overall Width:

Between 0.422 inches and 0.454 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.310 inches and 0.314 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.310 inches and 0.314 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Bsm single mating end

Contact Removability:

Removable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Terminal Type:

Pin single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping



Precious Material And Location: Contact surface gold and shell surface silver Precious Material And Weight: 0.005 gold grains, troy and 0.100 silver grains, troy Precious Material: Gold and silver Shelf Life: N/a Unit Of Measure: --Demilitarization: No

A039b0