Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-776-7162

| Thread Direction: |
|--|
| Right-hand |
| Overall Length: |
| 3.161 inches |
| Overall Diameter: |
| 1.344 inches |
| Cable Entrance Diameter: |
| 0.625 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 41.0 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 500.0 single mating end single contact grouping |
| Contact Maximum Dc Voltage Rating In Volts: |
| 700.0 single mating end single contact grouping |
| Connector Locking Method: |
| Internally threaded coupling nut |
| Connector Cable Strain Relief Method: |
| Cable clamp |
| Thread Size: |
| 1.250 inches |
| Insert Material: |
| Rubber single mating end |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Anodize |
| Included Contact Quantity: |
| 5 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5935-00-776-7162

Electrical Plug Connector - Page 2 of 2

Demilitarization:

No

Fiig:

A039b0

