NSN 5935-00-776-7210

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-776-7210

Body Style:
Straight shape
Overall Length:
0.610 inches
Overall Height:
2.484 inches
Overall Width:
0.609 inches
Unthreaded Mounting Hole Diameter:
0.093 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.307 inches and 1.317 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.338 inches and 0.348 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
34 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Shell Type:
Solid
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping or copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:
Qq-b-626, comp 22 federal specification single material response single mating end single contact grouping
Shell Material:
Aluminum alloy

NSN 5935-00-776-7210

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:	
Anodize	
Insert Material Specification:	
Mil-m-14, type sdg-f military specification single material response single mating end	
Included Contact Quantity:	
34 single mating end single contact grouping	
Included Contact Type:	
Round pin single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.034 gold grains, troy	
Precious Material:	
Gold	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	
Mil-m-14 spec.	