NSN 5935-00-776-7908

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-776-7908 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 1.875 inches **Overall Diameter:** Between 2.047 inches and 2.077 inches **Environmental Protection:** Vibration resistant and salt water resistant and hermetic **Distance From Mounting Shoulder To Front Face:** 1.094 inches **Mounting Facility Thickness:** 0.422 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 24-28 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 200.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 250.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell

Thread Size:

1.500 inches and 1.500 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-00-776-7908

Electrical Receptacle Connector - Page 2 of 2



Contact Material:
Steel single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Ceramic single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, class c federal specification single treatment response
Included Contact Quantity:
24 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/double flat
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.024 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0