

Electrical Receptacle Connector - Page 1 of 2	AGIUD 350
View Online at https://aerobasegroup.com/nsn/5935-00-779-5272	
Body Style:	
Straight edge type	

Overall Length:

5.620 inches

Overall Height:

0.453 inches

Overall Width:

0.531 inches

Unthreaded Mounting Hole Diameter:

0.128 inches

Distance Between Mounting Facility Centers:

5.352 inches

Board Accommodated Length:

5.030 inches single board

Board Accommodated Width:

0.074 inches

Mating End Quantity:

Contact Position Arrangement Style:

Bridged contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

10.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

675.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Contact Material Specification:

Astm b139-58 assn standard single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end

NSN 5935-00-779-5272

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
47 single mating end single contact grouping
Included Contact Type:
Spring pincers single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.047 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

Mil-m-14 spec.

Mil-std (military Standard):