

View Online at <https://aerobasegroup.com/nsn/5935-00-779-6156>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Rectangular shape w/center jack

Overall Length:

0.600 inches

Overall Height:

0.703 inches

Overall Width:

0.600 inches

Body Height:

0.234 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end 1st contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end 1st contact grouping

Polarization Method:

Contact and jackscrew

Connector Locking Method:

Jackscrew

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Terminal Location:

Back single mating end 1st contact grouping

Contact Material:

Copper alloy single mating end 1st contact grouping

Contact Surface Treatment:

Gold single mating end 1st contact grouping

Insert Material:

Plastic diallyl phthalate single mating end and glass fiber single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end 1st contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Solder well single mating end 1st contact grouping

Insert Material Specification:

Mil-g-45204, type sdg-f military specification all material responses single mating end

Included Contact Quantity:

30 single mating end 1st contact grouping

Special Features:

Polarizing pins installed in contact positions a and b

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.030 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.