NSN 5935-00-779-6401

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-779-6401

view Online at https://aerobasegroup.com/nsn/5935-00-779-6401
Body Style:
Straight shape
Overall Length:
Between 1.198 inches and 1.228 inches
Overall Height:
0.656 inches
Overall Width:
Between 0.479 inches and 0.509 inches
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.125 inches
Distance Between Mounting Facility Centers:
Between 0.969 inches and 0.999 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
9 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Tin
Insert Material Specification:

Mil-m-14, type sdg military specification single material response single mating end

Included Contact Quantity:

9 single mating end single contact grouping

NSN 5935-00-779-6401

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
$0.009 \ \text{gold grains}, \ \text{troy} \ \text{and} \ 0.009 \ \text{silver grains}, \ \text{troy}$
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0

Mil-m-14 spec.

Mil-std (military Standard):