NSN 5935-00-779-7601

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-779-7601

D. J. O. J.
Body Style:
Straight shape
Overall Length:
1.625 inches
Overall Width:
0.562 inches
Environmental Protection:
Humidity resistant and shock resistant and thermal shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.143 inches
Distance Between Mounting Facility Centers:
1.312 inches
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Contact
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Back single mating end single contact grouping Contact Surface Treatment:
Back single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
Back single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:
Back single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end
Back single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Contact Surface Treatment Specification:
Back single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Contact Surface Treatment Specification: Mil-g-45294 type 1, grade c military specification single treatment response single mating end single contact grouping
Back single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Contact Surface Treatment Specification: Mil-g-45294 type 1, grade c military specification single treatment response single mating end single contact grouping Terminal Type:
Back single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Contact Surface Treatment Specification: Mil-g-45294 type 1, grade c military specification single treatment response single mating end single contact grouping Terminal Type: Solder well single mating end single contact grouping
Back single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Contact Surface Treatment Specification: Mil-g-45294 type 1, grade c military specification single treatment response single mating end single contact grouping Terminal Type: Solder well single mating end single contact grouping Shell Material:
Back single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Contact Surface Treatment Specification: Mil-g-45294 type 1, grade c military specification single treatment response single mating end single contact grouping Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy
Back single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Contact Surface Treatment Specification: Mil-g-45294 type 1, grade c military specification single treatment response single mating end single contact grouping Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:
Back single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Contact Surface Treatment Specification: Mil-g-45294 type 1, grade c military specification single treatment response single mating end single contact grouping Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium
Back single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Contact Surface Treatment Specification: Mil-g-45294 type 1, grade c military specification single treatment response single mating end single contact grouping Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:

Mil-m-14 ty sdg-f military specification single material response single mating end

NSN 5935-00-779-7601

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
26 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.026 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms24020 government standard
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:

A039b0

, 100000

Mil-std (military Standard):

Mil-g-45294 spec.