

View Online at <https://aerobasegroup.com/nsn/5935-00-779-8286>

Body Style:

Angle, shape, internal coupling

Overall Height:

Between 1.160 inches and 1.200 inches

Cable Entrance Diameter:

0.257 inches

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Connector Cable Strain Relief Method:

Conduit nut

End Application:

Mars class t-afs 1, whidbey island class lsd, kilauea class t-ae 26, austin ship class lpd-4 amphibious transport docks, blue ridge class lcc-19, emory s. Land class as, supply class aoe

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Criticality Code Justification:

Feat

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Special Features:

Weapon system essential

Precious Material And Location:

Contact and body surfaces silver

Precious Material And Weight:

0.105 silver grains, troy

Precious Material:

Silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0