NSN 5935-00-779-8606

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-779-8606

View Online at https://aerobasegroup.com/nsn/5935-00-779-8606
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
2.753 inches
Overall Diameter:
1.531 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Cable Entrance Diameter:
0.519 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
20-39 single mating end
Contact Removability:
Removable single mating end all contact groupings
Contact Maximum Ac Voltage Rating In Volts:
600.0 single mating end all contact groupings
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Connector Cable Strain Relief Method:
Cable clamp
Terminal Location:
Back single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings and copper single mating end all contact groupings
Terminal Type:
Crimp single mating end all contact groupings Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
wy p +10, type 2, or o rederal opeolitication of the attribution response

Included Contact Quantity:

37 single mating end 2nd contact grouping

NSN 5935-00-779-8606

Mil-std (military Standard):

Mil-c-26482 spec.

Electrical Plug Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.047 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms3126 government standard
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0