Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-781-2831

Thread Class:
2a
Body Style:
Straight shape, external coupling
Overall Length:
1.110 inches
Cable Entrance Diameter:
0.212 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Connector Cable Strain Relief Method:
Crimp type
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Included Contact Quantity:
1 single mating end single contact grouping
Special Features:
Supplied with 2 hex nuts, one @flat washer and one inter. Tooth lockwasher
Precious Material And Location:
Contact and shell surfaces silver
Precious Material:
Silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5935-00-781-2831

Electrical Receptacle Connector - Page 2 of 2

**Fiig:** A039b0

