Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-781-9013

Thread Class
Thread Class:
2a and 2b
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
Between 1.050 inches and 1.070 inches
Overall Height:
Between 0.490 inches and 0.510 inches
Overall Width:
Between 0.260 inches and 0.280 inches
Environmental Protection:
Thermal shock resistant and humidity resistant and vibration resistant and shock resistant and corrosion resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
20 20-20 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Operating Tempurature Rating:
Between -55.0 degrees celsius and 125.0 degrees celsius
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate glass filled single mating end

NSN 5935-00-781-9013 Electrical Plug Connector - Page 2 of 2



Contact Surface	Treatment Specification:
Mil-g-45204 militar	ry specification 1st treatment response single mating end single contact grouping
Terminal Type:	
Solder well single i	mating end single contact grouping
Insert Material Sp	pecification:
Mil-m-14, type gdi-	-30 military specification single material response single mating end
Included Contact	Quantity:
20 single mating e	nd single contact grouping
Included Contact	Туре:
Round pin single m	nating end single contact grouping
Precious Material	And Location:
Contact surfaces g	Jold
Precious Material	And Weight:
0.020 gold grains,	troy
Precious Material	1:
Gold	
Thread Series De	signator:
Unef	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military S	Standard):
Mil-g-45204 spec.	