NSN 5935-00-782-4721

Tip Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-782-4721 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Red **Body Style:** Threaded bushing mounted **Overall Length:** Between 0.922 inches and 1.000 inches **Mounting Bushing Length:** Between 0.375 inches and 0.438 inches **Body Length:** 0.617 inches **Overall Diameter:** Between 0.250 inches and 0.312 inches **Bushing Accommodation Hole Shape:** Round **Accommodated Finger Type:** Test prod single finger **Finger Accommodation Diameter:** 0.079 inches and 0.081 inches single finger **Finger Accommodation Length:** 0.500 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.250 inches **Current Rating In Amps:** 5.0 **Mounting Facility Type And Quantity:** 1 bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.250 inches **Criticality Code Justification:** Feat **Terminal Type:** Tab, solder lug **Special Features:** Item must comply with requirements of defense electronics supply center production standard no. L00388

NSN 5935-00-782-4721

Tip Jack - Page 2 of 2



| Material: |
|-----------------------------------|
| Copper alloy terminal |
| Material: |
| Plastic insulator |
| Precious Material And Location: |
| Spring and terminal surfaces gold |
| Precious Material: |
| Gold |
| Surface Treatment: |
| Gold terminal |
| Surface Treatment: |
| Gold spring |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| VU3400 |