## NSN 5935-00-782-4729

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-782-4729 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.240 inches **Overall Height:** 1.030 inches **Overall Width:** 1.030 inches **Unthreaded Mounting Hole Diameter:** 0.129 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.812 inches **Distance From Mounting Shoulder To Front Face:** 0.717 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 12-12 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Externally threaded shell **Thread Length:** 0.286 inches Thready Qty Per Inch (tpi): 0 and 20 **Thread Size:** 

0.875 inches and 0.750 inches

**Insert Material:** 

Plastic single mating end

## NSN 5935-00-782-4729

Electrical Receptacle Connector Body - Page 2 of 2



| Shell Material:   |
|---|
| Aluminum alloy 6061   |
| Shell Surface Treatment:  |
| Anodize   |
| Shell Surface Treatment Specification:                              |
| Mil-a-8625, type 1 military specification single treatment response |
| Shell Material Specification:                                       |
| Qq-a-367 federal specification single material response             |
| Thread Series Designator:   |
| Unef and unef   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A039b0  |
| Mil-std (military Standard):  |
| Mil-a-8625 spec.  |