## NSN 5935-00-782-6156

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-782-6156 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 1.222 inches **Overall Diameter:** 1.875 inches **Environmental Protection:** Moisture resistant **Distance From Mounting Shoulder To Front Face:** Between 0.717 inches and 0.749 inches **Mounting Facility Thickness:** 0.093 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 61-3 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 41.0 single mating end 1st contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Ball Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.625 inches **Terminal Location:** Back single mating end all contact groupings

**Insert Material:** 

Rubber synthetic single mating end

## NSN 5935-00-782-6156

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
49 single mating end 2nd contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end all contact groupings
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0