**Body Style:** 

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-782-6930

## Straight shape **Overall Length:** Between 0.678 inches and 0.698 inches **Overall Height:** Between 0.990 inches and 1.010 inches **Overall Width:** Between 1.990 inches and 2.010 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.495 inches and 0.505 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.775 inches and 1.785 inches **Distance From Mounting Shoulder To Front Face:** Between 0.458 inches and 0.478 inches Mating End Quantity: 1 **Contact Position Arrangement Style:** 32 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic melamine single mating end **Terminal Type:** Tab, solder lug single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate

## NSN 5935-00-782-6930

Electrical Receptacle Connector - Page 2 of 2



**Included Contact Quantity:** 32 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.032 gold grains, troy and 0.032 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0