

View Online at <https://aerobasegroup.com/nsn/5935-00-782-6938>

**Body Style:**

Straight shape, rectangular

**Distance Between Mounting Facility Centers:**

3.281 inches

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

"3, 5-15" all mating ends

**Contact Removability:**

Nonremovable all mating ends all contact groupings

**Contact Maximum Current Rating In Amps:**

15.0 all mating ends all contact groupings

**Contact Maximum Dc Voltage Rating In Volts:**

125.0 all mating ends all contact groupings

**Polarization Method:**

Contact

**Shell Type:**

Solid

**Terminal Location:**

Side all mating ends all contact groupings

**Contact Surface Treatment:**

Nickel all mating ends all contact groupings

**Insert Material:**

Plastic all mating ends

**Contact Surface Treatment Specification:**

Qq-n-290, class 2, type 6 federal specification single treatment response all mating ends all contact groupings

**Terminal Type:**

Screw all mating ends all contact groupings

**Included Contact Quantity:**

2 single mating end 1st contact grouping

**Special Features:**

Mounting strap plated nf0023

**Test Data Document:**

81348-w-c-596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81348-w-c-596/12 government specification

**Specification Or Standard:**

D7 style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0