

View Online at <https://aerobasegroup.com/nsn/5935-00-782-6938>

Body Style:

Straight shape, rectangular

Distance Between Mounting Facility Centers:

3.281 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

"3, 5-15" all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

15.0 all mating ends all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

125.0 all mating ends all contact groupings

Polarization Method:

Contact

Shell Type:

Solid

Terminal Location:

Side all mating ends all contact groupings

Contact Surface Treatment:

Nickel all mating ends all contact groupings

Insert Material:

Plastic all mating ends

Contact Surface Treatment Specification:

Qq-n-290, class 2, type 6 federal specification single treatment response all mating ends all contact groupings

Terminal Type:

Screw all mating ends all contact groupings

Included Contact Quantity:

2 single mating end 1st contact grouping

Special Features:

Mounting strap plated nf0023

Test Data Document:

81348-w-c-596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81348-w-c-596/12 government specification

Specification Or Standard:

D7 style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0