

View Online at <https://aerobasegroup.com/nsn/5935-00-782-7064>

Thread Class:

2a

Thread Direction:

Right-hand

Electrical Insulation Feature:

Insulated completely

Identification Code Color:

Black

Body Style:

Dual threaded bushing mounted

Overall Height:

Between 0.860 inches and 0.900 inches

Mounting Bushing Length:

0.500 inches

Body Length:

Between 0.860 inches and 0.900 inches

Body Width:

Between 0.360 inches and 0.400 inches

Body Height:

0.750 inches

Bushing Accommodation Hole Shape:

Double round plain

Maximum Voltage Rating In Volts:

1500.0 dc

Accommodated Finger Type:

Test prod all fingers

Finger Accommodation Diameter:

0.099 inches and 0.109 inches all fingers

Finger Accommodation Length:

0.370 inches and 0.410 inches all fingers

Center To Center Distance Between Finger Accommodations:

Between 0.490 inches and 0.510 inches

Bushing Thru-hole Accommodation Diameter:

0.250 inches

Center To Center Distance Between Bushing Thru-hole Accommodations:

0.500 inches

Current Rating In Amps:

5.0

Mounting Facility Type And Quantity:

2 bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Terminal Type:

Turret

Material:

Plastic, polycarbonate insulator

Material:

Plastic polycarbonate insulator

Precious Material And Location:

Spring and terminal surfaces gold

Precious Material:

Gold

Surface Treatment:

Gold and nickel terminal

Surface Treatment:

Gold spring and nickel spring

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03400