

View Online at <https://aerobasegroup.com/nsn/5935-00-782-7064>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Electrical Insulation Feature:**

Insulated completely

**Identification Code Color:**

Black

**Body Style:**

Dual threaded bushing mounted

**Overall Height:**

Between 0.860 inches and 0.900 inches

**Mounting Bushing Length:**

0.500 inches

**Body Length:**

Between 0.860 inches and 0.900 inches

**Body Width:**

Between 0.360 inches and 0.400 inches

**Body Height:**

0.750 inches

**Bushing Accommodation Hole Shape:**

Double round plain

**Maximum Voltage Rating In Volts:**

1500.0 dc

**Accommodated Finger Type:**

Test prod all fingers

**Finger Accommodation Diameter:**

0.099 inches and 0.109 inches all fingers

**Finger Accommodation Length:**

0.370 inches and 0.410 inches all fingers

**Center To Center Distance Between Finger Accommodations:**

Between 0.490 inches and 0.510 inches

**Bushing Thru-hole Accommodation Diameter:**

0.250 inches

**Center To Center Distance Between Bushing Thru-hole Accommodations:**

0.500 inches

**Current Rating In Amps:**

5.0

**Mounting Facility Type And Quantity:**

2 bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.164 inches

**Terminal Type:**

Turret

**Material:**

Plastic, polycarbonate insulator

**Material:**

Plastic polycarbonate insulator

**Precious Material And Location:**

Spring and terminal surfaces gold

**Precious Material:**

Gold

**Surface Treatment:**

Gold and nickel terminal

**Surface Treatment:**

Gold spring and nickel spring

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03400