Plastic single mating end

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-782-7616

Thread Class:
2a and 2b
Thread Direction:
Right-hand
Body Style:
Hood, side opening w/clamp
Overall Height:
Between 1.980 inches and 2.140 inches
Environmental Protection:
Heat resistant and moisture resistant and pressure proof and salt water resistant and vibration resistant
Cable Entrance Diameter:
Between 0.260 inches and 0.300 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
26 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Shell Type:
Hood, side opening
Connector Locking Method:
Jackscrew-socket
Connector Cable Strain Relief Method:
Cable clamp
Thread Size:
0.099 inches and 0.099 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Direction structure and

NSN 5935-00-782-7616 Electrical Plug Connector - Page 2 of 2



Solder well s	ingle mating end single contact grouping
Shell Materi	al:
Aluminum all	loy
Shell Surfac	e Treatment:
Anodize	
Shell Surfac	e Treatment Specification:
Mil-f-14072, 1	finish e516 military specification single treatment response
nsert Mater	ial Specification:
Mil-m-18794	, ty sdi-5 military specification single material response single mating end
ncluded Co	ontact Quantity:
26 single ma	ting end single contact grouping
Included Co	ontact Type:
Round pin si	ngle mating end single contact grouping
Precious Ma	aterial And Location:
Contact surfa	aces gold
Precious Ma	aterial And Weight:
0.026 gold gi	rains, troy
Precious Ma	aterial:
Gold	
Thread Serie	es Designator:
Unc and unc	
Shelf Life:	
N/a	
Unit Of Mea	sure:
Demilitariza	tion:
No	
Fiig:	
A039b0	
Mil-std (mili	tary Standard):
Mil-m-18794	spec.