

View Online at <https://aerobasegroup.com/nsn/5935-00-782-7621>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Angle, shape, internal coupling

**Overall Length:**

1.563 inches

**Overall Height:**

1.359 inches

**Overall Diameter:**

0.750 inches

**Cable Entrance Diameter:**

0.442 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

N single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Contact Maximum Frequency Rating:**

10000.0 megahertz single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Connector Cable Strain Relief Method:**

Compression nut

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Thread Length:**

0.158 inches

**Thread Size:**

0.625 inches

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic tetrafluoroethylene single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 2 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Silver

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Test Data Document:**

24930-g350133 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.