NSN 5935-00-783-3865

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-783-3865 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Rectangular shape **Overall Length:** 2.060 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.812 inches **Overall Height:** 0.590 inches **Overall Width:** 0.720 inches **Environmental Protection:** Vibration resistant **Unthreaded Mounting Hole Diameter:** 0.090 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.562 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 75 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Jackscrew-socket Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

NSN 5935-00-783-3865

Electrical Receptacle Connector - Page 2 of 2



| C. | onta | act S | Surfa | ice Ti | reatm | ent. |
|----|-------|-------|-------|--------|-------|--------|
| v | Ulita | ıcı v | Julia | 166 11 | Caui | ICIIL. |

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate and glass fiber single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-p-19833, type gdi-30 military specification all material responses single mating end

Unable To Decode:

Unable to decode and unable to decode and unable to decode and unable to decode

Included Contact Quantity:

75 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Jackscrew type - male and location lefthand top, and jackscrew type-female and location lefthand top and jackscrew type - female and location left hand bottom and jackscrew type-male and location-right hand bottom

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.075 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.