

View Online at <https://aerobasegroup.com/nsn/5935-00-783-5369>

Body Style:

Straight shape, internal coupling w/backshell

Overall Length:

1.513 inches

Overall Diameter:

1.281 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

28-12 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

60.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Included Contact Quantity:

26 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.026 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-26482 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0