

View Online at <https://aerobasegroup.com/nsn/5935-00-783-5385>

Thread Class:

2a and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

2.125 inches

Overall Diameter:

1.344 inches

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

18-8 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

41.0 single mating end 1st contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Thread Length:

0.290 inches and 0.664 inches

Operating Temperature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thready Qty Per Inch (tpi):

18 and 18

Thread Size:

1.062 inches and 1.125 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and silver single mating end all contact groupings

Insert Material:

Rubber chloroprene class cr single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end all contact groupings and qq-s-365 federal specification 2nd treatment response single mating end all contact groupings

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Included Contact Quantity:

7 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.012 gold grains, troy and 0.012 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.