## NSN 5935-00-784-3110

Tip Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-784-3110 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Black **Body Style:** Threaded bushing mounted **Overall Length:** 1.125 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.531 inches **Overall Diameter:** 0.312 inches **Bushing Accommodation Hole Shape:** Round **Maximum Voltage Rating In Volts:** 700.0 ac **Accommodated Finger Type:** Test prod single finger **Finger Accommodation Diameter:** 0.080 inches single finger **Finger Accommodation Length:** 0.531 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.250 inches Capacitance In Picofarads: **Current Rating In Amps:** 

5.0 **Mounting Facility Type And Quantity:** 1 bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.250 inches **Terminal Type:** Tab, solder lug

## **NSN 5935-00-784-3110** Tip Jack - Page 2 of 2



Material:
Plastic, polyamide insulator
Material:
Plastic polyamide insulator
Precious Material And Location:
Spring surfaces silver
Precious Material:
Silver
Surface Treatment:
Tin terminal
Surface Treatment:
Tin terminal
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No
Fiig:

A03400