## NSN 5935-00-784-3675

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-784-3675 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** Between 0.900 inches and 0.904 inches **Environmental Protection:** Moisture proof and vibration resistant **Distance From Mounting Shoulder To Front Face:** Between 0.350 inches and 0.390 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Dm single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet pin **Thread Size:** 0.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Plastic tetrafluoroethylene single mating end **Terminal Type:** Turret single mating end single contact grouping **Contact Material Specification:** Qq-c-530, 1/2 hard federal specification single material response single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:** 

Silver

## NSN 5935-00-784-3675

Electrical Receptacle Connector - Page 2 of 2



<b>/</b> :

1 single mating end single contact grouping

**Bushing Accommodation Hole Shape:** 

Round w/double flat

**Included Contact Type:** 

Coaxial socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces and shell surface silver

**Precious Material And Weight:** 

0.105 silver grains, troy

•

**Precious Material:** 

Silver

**Thread Series Designator:** 

Unef

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0