

View Online at <https://aerobasegroup.com/nsn/5935-00-784-5247>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling w/strain relief

Body Length:

6.000 inches

Overall Diameter:

2.030 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and shock resistant and cold resistant and heat resistant and explosion proof

Cable Entrance Diameter:

Between 0.750 inches and 1.250 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

28-21 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

280.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Cable clamp

Thread Length:

0.625 inches

Operating Temperature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Features Provided:

Pre-tinned terminal

Thready Qty Per Inch (tpi):

18

Thread Size:

1.750 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Rubber single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade b military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 1, grade b federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification all treatment responses

Included Contact Quantity:

37 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.037 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.