Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-785-8281

### Body Style:

Straight edge type w/mounting flange

## **Overall Length:**

Between 2.975 inches and 2.995 inches

## **Overall Height:**

0.656 inches

### **Overall Width:**

Between 0.318 inches and 0.338 inches

### **Unthreaded Mounting Hole Diameter:**

Between 0.125 inches and 0.131 inches

### Distance Between Mounting Facility Centers:

Between 2.740 inches and 2.760 inches

### **Board Accommodated Length:**

2.345 inches single board and 2.355 inches single board

### **Board Accommodated Width:**

Between 0.255 inches and 0.275 inches

## Mating End Quantity:

1

## Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

### Contact Removability:

Removable single mating end single contact grouping

# **Contact Maximum Current Rating In Amps:**

3.5 single mating end single contact grouping

### **Polarization Method:**

Contact to contact polarizing keys

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

### **Insert Material:**

Plastic diallyl phthalate single mating end

# **Terminal Type:**

Tab, solder lug single mating end single contact grouping

### Insert Material Specification:

Mil-m-19833, type gdi-30f military specification single material response single mating end

### Included Contact Quantity:

22 single mating end single contact grouping

### **Included Contact Type:**

Bifurcated accordian leaf spring single mating end single contact grouping



Precious Material And Location:

Contact surfaces gold

**Precious Material And Weight:** 

0.022 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.