# NSN 5935-00-785-9008

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-785-9008

view Online at https://aerobasegroup.com/nsn/5935-00-785-9008
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
1.900 inches
Overall Diameter:
Between 1.094 inches and 1.141 inches
Environmental Protection:
Moisture resistant and vibration resistant
Cable Entrance Diameter:
0.375 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
14-19 single mating end
Contact Removability:
Removable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
7.5 single mating end 3rd contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
165.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Connector Cable Strain Relief Method:
Cable clamp
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Nickel alloy single mating end 2nd contact grouping
Contact Surface Treatment:
Gold single mating end 3rd contact grouping and silver single mating end 3rd contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy

**Shell Surface Treatment:**Cadmium and chromate

## NSN 5935-00-785-9008

Electrical Plug Connector - Page 2 of 2



## **Included Contact Quantity:**

2 single mating end 2nd contact grouping

### **Included Contact Type:**

Round socket single mating end all contact groupings

### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

## **Precious Material And Weight:**

0.019 gold grains, troy and 0.019 silver grains, troy

#### **Precious Material:**

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0