NSN 5935-00-787-7257

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-787-7257 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand and right-hand **Overall Length:** 1.438 inches **Overall Diameter:** 0.975 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Polarization Method:** Contact Shell Type: Solid **Connector Locking Method:** Internally threaded coupling nut Thready Qty Per Inch (tpi): 20 and 20 **Thread Size:** 0.875 inches and 1.000 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Included Contact Quantity:

5 single mating end single contact grouping

NSN 5935-00-787-7257

Electrical Receptacle Connector - Page 2 of 2



Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.005 gold grains, troy and 0.005 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0