

View Online at <https://aerobasegroup.com/nsn/5935-00-789-0035>

**Body Style:**

Straight shape, rectangular

**Overall Length:**

3.225 inches

**Overall Height:**

0.882 inches

**Overall Width:**

1.275 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.125 inches

**Distance Between Mounting Facility Centers:**

2.875 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

24 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

750.0 single mating end single contact grouping

**Polarization Method:**

Shell

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Nickel

**Shell Guide Type And Location Designator:**

2 pin

**Included Contact Quantity:**

24 single mating end single contact grouping

**Included Contact Type:**

Leaf spring single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.024 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.