## NSN 5935-00-789-7761

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-789-7761

Body Style:
Straight shape
Overall Length:
1.556 inches
Overall Height:
0.656 inches
Overall Width:
0.509 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
Between 1.307 inches and 1.317 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
"2, 15" single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
On-n-416 type 2 class 2 federal specification single treatment response

**Insert Material Specification:** 

Mil-m-19833, type gdi-30f military specification single material response single mating end

## NSN 5935-00-789-7761

Electrical Receptacle Connector - Page 2 of 2



## **Included Contact Quantity:**

15 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:** 

0.015 gold grains, troy and 0.015 silver grains, troy

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.