

View Online at <https://aerobasegroup.com/nsn/5935-00-791-0640>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, flush mount

**Overall Length:**

Between 1.099 inches and 1.119 inches

**Overall Height:**

Between 3.927 inches and 3.947 inches

**Overall Width:**

Between 3.365 inches and 3.385 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.995 inches and 1.005 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 2.870 inches and 2.880 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.052 inches and 0.072 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

78 single mating end

**Contact Removability:**

Nonremovable all mating ends single contact grouping

**Contact Maximum Current Rating In Amps:**

10.0 all mating ends single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Screw

**Thread Size:**

0.250 inches

**Terminal Location:**

Back all mating ends single contact grouping

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Gold all mating ends single contact grouping and silver all mating ends single contact grouping

**Insert Material:**

Plastic melamine all mating ends or plastic phenolic all mating ends

**Terminal Type:**

Solder well all mating ends single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.156 gold grains, troy and 0.156 silver grains, troy

**Precious Material:**

Gold and silver

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0