## NSN 5935-00-791-5442



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-791-5442 **Body Style:** Straight shape, external coupling strain relief **Overall Height:** 1.562 inches **Overall Width:** 1.562 inches **Body Length:** 1.970 inches **Environmental Protection:** Moisture resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches **Cable Entrance Diameter:** 1.440 inches **Distance From Mounting Shoulder To Front Face:** 0.562 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 22-48 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 45.0 Shell Type: Solid

**Connector Locking Method:** 

Bayonet pin

**Connector Cable Strain Relief Method:** 

Cable clamp

**Terminal Location:** 

Back single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

## NSN 5935-00-791-5442

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Shell Surface Treatment Specification:
Mil-a-8625a military specification single treatment response
Insert Material Specification:
Mil-m-14 military specification single material response single mating end
Included Contact Quantity:
48 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.