NSN 5935-00-793-8056

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-793-8056

View Online at https://aerobasegroup.com/nsn/5935-00-793-8056
Body Style:
Angle, shape, internal coupling
Overall Length:
0.812 inches
Overall Height:
0.750 inches
Cable Entrance Diameter:
0.252 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
Dm single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
180.0 and 180.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Connector Cable Strain Relief Method:
Conduit nut
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic tetrafluoroethylene single mating end
Terminal Type:
Crimp and solder single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:

Gold and silver

Included Contact Quantity:

1 single mating end single contact grouping

NSN 5935-00-793-8056

Electrical Plug Connector - Page 2 of 2



Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold and contact surface silver

Precious Material And Weight:

0.005 gold grains, troy and 0.005 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0