Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-797-1879

Body	Style:
Straig	ht shape
Overa	II Length:
2.469	inches
Overa	III Height:
0.980	inches
Overa	all Width:
Betwe	en 0.870 inches and 0.880 inches
Unthr	eaded Mounting Hole Diameter:
Betwe	en 0.114 inches and 0.120 inches
Distar	nce Between Mounting Facility Centers:
2.125	inches
Mating	g End Quantity:
1	
Conta	act Position Arrangement Style:
16 sin	gle mating end
Conta	act Removability:
Nonre	movable single mating end single contact grouping
Conta	act Maximum Current Rating In Amps:
5.0 sir	ngle mating end single contact grouping
Polari	ization Method:
Mating	g end
Termi	nal Location:
Back s	single mating end single contact grouping
Conta	act Material:
Coppe	er alloy single mating end single contact grouping
Conta	act Surface Treatment:
Gold s	single mating end single contact grouping
Insert	Material:
Plastic	c diallyl phthalate single mating end
Termi	inal Type:
Tab, s	solder lug single mating end single contact grouping
Conta	act Material Specification:
Qq-b-7	750, comp a, hard federal specification single material response single mating end single contact grouping
Insert	Material Specification:
Mil-m-	14, type mdg military specification single material response single mating end
Includ	ded Contact Quantity:
16 sin	gle mating end single contact grouping
Includ	led Contact Type:
Round	d pin single mating end single contact grouping
Speci	al Features:
Polariz	zing by 7 barriers



Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.016 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.