Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-797-7910



| Thread Class:   |
|---|
| 2b  |
| Thread Direction:   |
| Right-hand  |
| Body Style:   |
| Angle shape w/cable clamp                                   |
| Overall Diameter:   |
| 1.484 inches  |
| Body Angle In Deg:  |
| 90.0  |
| Environmental Protection:                                   |
| Moisture proof and salt water resistant and vibration proof |
| Cable Entrance Diameter:                                    |
| 0.500 inches  |
| Threaded Device Type:                                       |
| Coupling facility   |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:                         |
| 16-10 single mating end                                     |
| Contact Removability:                                       |
| Removable single mating end single contact grouping         |
| Contact Maximum Current Rating In Amps:                     |
| 41.0 single mating end single contact grouping              |
| Contact Maximum Ac Voltage Rating In Volts:                 |
| 500.0 single mating end single contact grouping             |
| Contact Maximum Dc Voltage Rating In Volts:                 |
| 700.0 single mating end single contact grouping             |
| Polarization Method:  |
| Keyway or multiple keyway                                   |
| Insert Position In Deg:                                     |
| 0.0   |
| Shell Type:   |
| Solid   |
| Connector Locking Method:                                   |
| Internally threaded coupling ring                           |
| Connector Cable Strain Relief Method:                       |
| Cable clamp   |
| Thread Size:  |
| 1.000 inches  |
| Terminal Location:  |
| Back single mating end single contact grouping              |

# NSN 5935-00-797-7910

Electrical Plug Connector - Page 2 of 2



### **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

### Insert Material:

Rubber single mating end

# Terminal Type:

Crimp single mating end single contact grouping

### Shell Material:

Aluminum alloy

# Shell Surface Treatment:

Cadmium

# Shell Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

### Included Contact Quantity:

3 single mating end single contact grouping

#### Included Contact Type:

Round socket single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

### Precious Material And Weight:

 $0.015\ gold\ grains,\ troy\ and\ 0.015\ silver\ grains,\ troy$ 

Precious Material:

Gold and silver

### Thread Series Designator:

Unef

Shelf Life:

N/a

```
Unit Of Measure:
```

---

#### Demilitarization:

No

Fiig:

A039b0