

View Online at <https://aerobasegroup.com/nsn/5935-00-799-8346>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, flush mount

Overall Length:

Between 1.099 inches and 1.119 inches

Overall Height:

Between 3.927 inches and 3.947 inches

Overall Width:

Between 3.365 inches and 3.385 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.995 inches and 1.005 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.870 inches and 2.880 inches

Distance From Mounting Shoulder To Front Face:

Between 0.052 inches and 0.072 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

C 1st mating end

Contact Removability:

Removable 2nd mating end 1st contact grouping

Contact Maximum Current Rating In Amps:

40.0 2nd mating end 2nd contact grouping

Shell Type:

Solid

Connector Locking Method:

Screw

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and silver single mating end all contact groupings

Insert Material:

Plastic melamine all mating ends or plastic phenolic all mating ends

Terminal Type:

Solder well 2nd mating end 3rd contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Special Features:

A1 and a2 contacts, side a, for rg-58/u, a3 for rg-8 and 225/u cable

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.037 gold grains, troy and 0.037 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0