

View Online at https://aerobasegroup.com/nsn/5935-00-800-0985

Body Style:

Rectangular shape

Overall Length:

Between 0.430 inches and 0.450 inches

Overall Height:

Between 0.740 inches and 0.760 inches

Overall Width:

Between 0.135 inches and 0.145 inches

Environmental Protection:

Moisture resistant and fire resistant

Unthreaded Mounting Hole Diameter:

Between 0.088 inches and 0.098 inches

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

7.5 single mating end all contact groupings

Connector Locking Method:

Friction

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and silver single mating end all contact groupings

Insert Material:

Plastic melamine single mating end

Contact Surface Treatment Specification:

Mil-g-45204, ty ii, cl 1 military specification 1st treatment response single mating end all contact groupings and qq-s-365, ty i, grade b federal specification 2nd treatment response single mating end all contact groupings

Terminal Type:

Solder well single mating end all contact groupings

Contact Material Specification:

Qq-b-750, comp a federal specification single material response single mating end 2nd contact grouping

Insert Material Specification:

Mil-m-14, ty mme military specification single material response single mating end

Included Contact Quantity:

1 single mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end 2nd contact grouping

Special Features:

Mounting hole on side of connector



Precious Material And Location: Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.002 gold grains, troy and 0.002 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.