Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-800-1595

Thread Class:
Al
Body Style:
Straight shape, external coupling
Overall Length:
1.531 inches
Overall Height:
2.500 inches
Overall Width:
2.500 inches
Environmental Protection:
Watertight
Unthreaded Mounting Hole Diameter:
Between 0.171 inches and 0.177 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.933 inches and 1.943 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.933 inches and 1.943 inches
Distance From Mounting Shoulder To Front Face:
Between 0.875 inches and 0.885 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
36-10 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thread Length:
0.625 inches
Thready Qty Per Inch (tpi):
16

## NSN 5935-00-800-1595

Electrical Receptacle Connector - Page 2 of 2



## **Thread Size:** 2.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 48 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Special Features:** Alternate insert position 125.0 deg **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.048 gold grains, troy and 0.048 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Uns Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0