## NSN 5935-00-801-2202

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-801-2202

**Thread Class:** 

2a and 2a

**Thread Direction:** 

Right-hand and right-hand

**Body Style:** 

Straight shape threaded

**Overall Length:** 

1.531 inches

**Overall Diameter:** 

Between 1.740 inches and 1.760 inches

**Environmental Protection:** 

Explosion proof and salt water resistant

**Distance From Mounting Shoulder To Front Face:** 

Between 1.146 inches and 1.166 inches

**Mounting Facility Thickness:** 

Between 0.094 inches and 0.250 inches

**Threaded Device Type:** 

Coupling facility and mounting bushing

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

18-1 single mating end

**Contact Removability:** 

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:** 

21.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:** 

500.0 single mating end 1st contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end 1st contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

70.0

Shell Type:

Solid

**Connector Locking Method:** 

Externally threaded shell

Thready Qty Per Inch (tpi):

10

Thread Size:

1.125 inches and 1.250 inches

## NSN 5935-00-801-2202

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Silver single mating end all contact groupings
Insert Material:
Rubber single mating end
Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
6 single mating end 2nd contact grouping
<b>Bushing Accommodation Hole Shape:</b>
Round
Included Contact Type:
Round pin single mating end all contact groupings
Special Features:
Double stud coupling
Precious Material And Location:
Contact surface silver
Precious Material And Weight:
0.010 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Uns and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0