

View Online at <https://aerobasegroup.com/nsn/5935-00-801-8317>

**Body Style:**

Straight shape, internal coupling w/strain relief

**Body Length:**

2.156 inches

**Overall Diameter:**

1.046 inches

**Environmental Protection:**

Humidity resistant and corrosion resistant and vibration resistant

**Cable Entrance Diameter:**

0.438 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

12-p single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Polarization Method:**

Key, multiple key groove

**Insert Position In Deg:**

50.0

**Shell Type:**

Solid

**Connector Locking Method:**

Push-pull

**Connector Cable Strain Relief Method:**

Cable clamp

**Operating Temperature Rating:**

Between -40.0 degrees celsius and 65.0 degrees celsius

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:**

Rubber synthetic single mating end

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Included Contact Quantity:**

12 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.012 gold grains, troy and 0.012 silver grains, troy

**Precious Material:**

Gold and silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0