

View Online at <https://aerobasegroup.com/nsn/5935-00-802-7980>

Body Style:

Straight shape

Overall Length:

1.250 inches

Overall Height:

0.380 inches

Overall Width:

0.440 inches

Environmental Protection:

Vibration resistant and heat resistant and cold resistant and shock resistant and corrosion resistant

Unthreaded Mounting Hole Diameter:

0.143 inches

Distance Between Mounting Facility Centers:

0.937 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

14 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

13.0 single mating end single contact grouping

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-533 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

Included Contact Quantity:

14 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.014 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.