

View Online at <https://aerobasegroup.com/nsn/5935-00-802-9129>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.542 inches

**Overall Height:**

Between 1.855 inches and 1.895 inches

**Overall Width:**

Between 1.855 inches and 1.895 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.060 inches and 0.066 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.500 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.500 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.719 inches and 0.735 inches

**Threaded Device Type:**

Back shell and coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

28-51 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

23.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thready Qty Per Inch (tpi):**

18 and 18

**Thread Size:**

1.625 inches and 1.750 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:**

Rubber single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Included Contact Quantity:**

12 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold and contact surfaces gold

**Precious Material And Weight:**

0.012 gold grains, troy and 0.012 silver grains, troy

**Precious Material:**

Gold and silver

**Thread Series Designator:**

Unef and uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0