

View Online at <https://aerobasegroup.com/nsn/5935-00-803-7330>

Body Style:

Straight shape w/clamp

Overall Height:

1.968 inches

Overall Diameter:

1.500 inches

Cable Entrance Diameter:

0.625 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

3 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

15.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

125.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

125.0 single mating end all contact groupings

Polarization Method:

Contact

Shell Type:

Armored

Connector Locking Method:

Contact twistlock

Connector Cable Strain Relief Method:

Cable clamp

End Application:

Agm-65a maverick missile; spruance class dd (963) ship

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Nickel single mating end all contact groupings

Insert Material:

Plastic phenolic single mating end

Criticality Code Justification:

Feat

Terminal Type:

Screw single mating end all contact groupings

Shell Material:

Steel

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 1, class 3 federal specification single treatment response

Insert Material Specification:

Mil-m-14, type cfg military specification 1st material response single mating end

Included Contact Quantity:

2 single mating end 2nd contact grouping

Special Features:

Weapon system essential

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.