

View Online at <https://aerobasegroup.com/nsn/5935-00-803-7330>

**Body Style:**

Straight shape w/clamp

**Overall Height:**

1.968 inches

**Overall Diameter:**

1.500 inches

**Cable Entrance Diameter:**

0.625 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

3 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

15.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

125.0 single mating end all contact groupings

**Contact Maximum Dc Voltage Rating In Volts:**

125.0 single mating end all contact groupings

**Polarization Method:**

Contact

**Shell Type:**

Armored

**Connector Locking Method:**

Contact twistlock

**Connector Cable Strain Relief Method:**

Cable clamp

**End Application:**

Agm-65a maverick missile; spruance class dd (963) ship

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Nickel single mating end all contact groupings

**Insert Material:**

Plastic phenolic single mating end

**Criticality Code Justification:**

Feat

**Terminal Type:**

Screw single mating end all contact groupings



**Shell Material:**

Steel

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 1, class 3 federal specification single treatment response

**Insert Material Specification:**

Mil-m-14, type cfg military specification 1st material response single mating end

**Included Contact Quantity:**

2 single mating end 2nd contact grouping

**Special Features:**

Weapon system essential

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.