Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-804-0619

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape threaded
Overall Length:
1.105 inches
Overall Diameter:
Between 1.922 inches and 1.954 inches
Distance From Mounting Shoulder To Front Face:
Between 0.868 inches and 0.900 inches
Mounting Facility Thickness:
Between 0.062 inches and 0.250 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
22-55 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
30.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thread Size:
1.500 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping



#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

#### Insert Material:

Rubber single mating end

## Terminal Type:

Solder well single mating end single contact grouping

### Shell Material:

Aluminum alloy

### Shell Surface Treatment:

Cadmium and chromate

# Included Contact Quantity:

25 single mating end single contact grouping

# Bushing Accommodation Hole Shape:

Round

### Included Contact Type:

Round pin single mating end single contact grouping

# Precious Material And Location:

Contact surfaces gold or contact surfaces silver and contact surfaces silver

### Precious Material And Weight:

 $0.025 \ \text{gold grains}, \ \text{troy} \ \text{and} \ 0.025 \ \text{silver grains}, \ \text{troy}$ 

Precious Material:

Gold and silver

# Thread Series Designator:

Unef

# Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A039b0